

myTEMP™ Mini CO₂



- + Digital control of temperature and CO₂
- + Compact, fits in most biological safety cabinets
- + 20L capacity, accepts bottles & flasks up to 2L
- + Heats & cools (room temp. -10 to 55°C)
- + Dual beam infrared CO₂ sensor



At only 13 inches wide, the myTemp Mini CO₂ is the smallest and most economical incubator for applications requiring CO₂ gas control. Its small footprint makes the incubator ideal for use inside of biological safety cabinets, isolating sensitive cultures or for any laboratory simply trying to conserve bench space. With a thick layer of high efficiency insulation surrounding the chamber, the incubator is also ideal for transportation of cells. Once power has been disconnected, the incubator maintains temperature levels within 10% of the set parameter for up to 1 hour*. In addition each model includes a 12V vehicle power adapter for operating the instrument in a car, boat, etc.

Both temperature and CO₂ percentage are digitally adjustable and displayed in real time on the large LED control panel. This panel also features a "Cal" function, for easy in-lab calibration of the temperature or CO₂. In addition, humidity (up to 80%) can be added to the chamber by inserting the included (stainless steel) humidity reservoir.

The CO₂ level is constantly monitored using dual beam infrared sensing technology. In the event of a drop in CO₂, audible and visual alarms are triggered, notifying the user of the error.

Despite its small size, the incubator features a relatively large 20L chamber with the capacity for flasks and bottles up to 2 liters. Two removable, stainless-steel shelves are included. The shelves are perforated to improve airflow within the chamber.

* If disconnected from the CO₂ supply, CO₂ percentage decreases by approx. 1% /30 min.

Technical Data

| | |
|---------------------------|---|
| Temp. Range: | Ambient -10°C to 55°C |
| Temp. Accuracy: | +/- 0.25°C (at 37°C) |
| Temp. Uniformity: | +/- 0.25°C (at 37°C) |
| Temp. Increments: | 0.1°C |
| CO ₂ Range: | 0 to 20% |
| CO ₂ Sensor: | Dual Beam IR |
| CO ₂ Accuracy: | 0.1% at 5% |
| Humidity: | 70 to 80% |
| Dimensions: | |
| Exterior: | 13.2 x 14.5 x 18.7 in. 33.5 x 37 x 47.5 cm |
| Interior: | 10.3 x 9.3 x 12.8 in. 26 x 23.5 x 32.5 cm |
| Capacity: | 20L or 0.8 cubic feet |
| Weight: | 15 lbs (6.5kg) |
| Electrical: | 100 - 240V, 50-60Hz* or 12V DC |

Ordering Information:

H2300-HC2*

MyTemp Mini CO₂ Digital Incubator

Includes two stainless steel shelves, 4mm & 6mm tubing, air filter, 12V vehicle adapter & stainless humidity reservoir

H2300-REG

Optional CO₂ gas regulator (regulates pressure from the gas tank to the incubator)

* With US power cord, for EU power cord, please add (-E)



Optional CO₂ regulator



Easy access, CO₂ input port

Benchmark 
Scientific

PO Box 709
Edison, NJ 08818
Phone: 908-769-5555 Fax: 732-313-7007
Web: www.BenchmarkScientific.com
Email: Info@BenchmarkScientific.com