



- Digital control up to 5.500 rpm / 1.690 xq
- Conserves valuable bench space
 - Includes adapters for common blood tubes (12 x 75 mm)





Includes rotor and accessories for all common blood and centrifuge tubes up to 5ml

The myFuge[™] 5D is a compact, mini-sized centrifuge with the capacity to accept tubes up to 5ml. The unique rotor design accepts both 5ml snap-cap and 5ml screw-cap centrifuge tubes, as well as 12 x 75 (5ml) blood collection tubes. In addition, the rotor has four positions for standard microtubes (1.5/2.0ml) and offers optional adapters for 2ml cryotubes, 0.2ml PCR tubes, and 0.5ml microtubes, making it one of the most versatile and compact centrifuges in its class.

The myFuge 5D offers digital speed control (up to 5,500 rpm). Time is also controlled (up to 99 min.) with a safety interlock to stop the centrifuge if the lid is opened during operation. With built in rcf conversion, speed can be set/displayed in rpm or rcf. The myFuge 5D also comes with a 2-year warranty.

Technical Data:

Speed: 5,500rpm / 1,690 xg Capacity:

4 x 5ml tubes & 4 x 1.5/2.0ml

4 x 1.8-5ml blood tubes

0 to 59 sec / 1 to 99 mins. Timer:

Dimensions: (WxDxH) 7.6 x 9 x 4.7 in. 19.4 x 22 x 12 cm

Weight: 4.4 lbs / 2 kg Electrical: 100 to 240V, 50-60Hz

Warranty: 2 Year



Accepts 5ml snap/screw cap tubes and 5ml blood tubes (12 x 75mm)

Benchma

Ordering Information:	
C2205*	myFuge 5D digital microcentrifuge with combination rotor, 4×5 ml & $4 \times 1.5/2.0$ ml
C1008-A5-6	0.5ml Adapter Pack, 6/pk
C1008-A2-6	0.2ml Adapter Pack, 6/pk
C1005-AC2	Adapter Pack, for Cryovials (0.5 to 2.0ml) and 12x32mm HPLC vials, 4/pk
C1005-T5	5ml centrifuge tube, clear, 200/pk (2 bags of 100)
C1005-SC5	5ml <i>sterile</i> centrifuge tube, clear, 200/pk. (10 bags of 20)
	*115V with US plug. To order in 230V, add (-E) to the item number.

Benchmark Scientific Inc. PO Box 709 Edison, NJ 08818 Phone: 908-769-5555 Fax: 908-222-1864 Web: www.BenchmarkScientific.com Email: Info@BenchmarkScientific.com