

# HC-24™

## Hematocrit Centrifuge



- 24-place rotor for hematocrit capillary tubes
- Built-in reading disc in lid for instant analysis
- Digital control of speed and time (RPM/RCF)
- Rapid acceleration and deceleration
- Quick-spin function



Digital display and control



24-place capillary rotor

The HC-24 is a powerful, compact centrifuge designed specifically for hematocrit determination. With a 24-place rotor for standard 75 mm capillary tubes, samples reach up to 14,328 xg for fast and accurate results. A built-in reading disc in the lid allows for immediate analysis, eliminating the need for separate accessories. The large digital display offers precise control of speed (rpm or rcf) and run time, with a timer range from 20 seconds to 99 minutes, or continuous.

Engineered for efficiency and ease of use, the HC-24 features rapid acceleration to max speed in under 20 seconds, safe deceleration in under 30 seconds, and whisper-quiet operation. A quick-spin function add further convenience to routine workflows.

### Technical Data

Speed:	1,000 to 12,000 rpm
Max RCF:	14,328 xg
Timer:	20 secs to 99 mins, cont.
Capacity:	24 x 75 mm capillary tubes
Acc./Dec.:	20 s (Accel.) 30 s (Decel.)
Dimensions: (WxDxH)	14 x 11 x 9.8 in 36 x 28 x 25 cm
Weight:	35 lbs / 16 kg
Electrical:	110 to 230V, 50-60Hz
Warranty:	2 Years

### Ordering Information

C3450-H HC-24 Hematocrit Centrifuge with 24-place capillary rotor

\*To order in 230V, add (-E) to the item number.

**Benchmark**  
Scientific



**Benchmark Scientific Inc.**  
PO Box 709  
Edison, NJ 08817  
Phone: 908-769-5555  
Fax: 908-222-1864

Web: [www.BenchmarkScientific.com](http://www.BenchmarkScientific.com)  
Email: [Info@BenchmarkScientific.com](mailto:Info@BenchmarkScientific.com)